


NOTES:

1. FOR USE WITH BELDEN 1694A CABLE.
2. FOR CABLING INSTRUCTIONS SEE 3-661-4
3. FOR CRIMPING USE DIE KTH-2255, OR KTH-2325.
4. INTERFACE PER MIL-STD-348, FIG 301.1, AS APPLICABLE.
5. MATERIALS:
  - INSULATOR-PTFE: PER ASTM D1710
  - GASKET-SILICONE RUBBER: PER A-A-59588
  - SPRING WASHER } BERYLLIUM COPPER PER ASTM B196
  - OUTER CONTACT }
  - K-GRIP SLEEVE: COMMERCIAL BRONZE PER ASTM B135
  - ALL OTHER METAL PARTS: BRASS PER ASTM B16
6. FINISHES:
  - CENTER CONTACT: .000050 GOLD PLATE PER ASTM B488 OVER .000050 NICKEL PER AMS-QQ-N-290
  - SPRING WASHER-.000200 SILVER PLATE PER B700 OVER .000020 COPPER PER ASTM B734 OR NICKEL PER AMS-QQ-N-290.
  - ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQN-290 OVER .000050 MIN COPPER PER ASTM B734
7. MARK PACKAGE: KINGS 2065-10-9
8. ELECTRICAL CHARACTERISTICS:
  - NOMINAL IMPEDANCE: 75 OHMS
  - WORKING VOLTAGE: 500 VRMS
  - FREQUENCY RANGE: DC TO 12 GHz
  - RETURN LOSS: -30 dB MAX TO 3.0 GHz
  - 20 dB MAX TO 6.0 GHz
9. COMPLIANT TO 3G/6G/12G SDI SMPTE REQUIREMENTS.

MARK: KINGS 2065-10-9  
YR'WK (DATE CODE)

2065-10-9

REVISIONS			
ISSUE	CHANGES		
4	CN 38027 E TML 07/07/00		
5	CN 38495 E TML 02/01/02		
6	CN 38637 E TML 08/22/02		
H	ER 14183 PSM 03/09/09		
J	ER 22156 DW 03/02/10		
K	CRIMPING TOOL ADDED KTH-2325 UPDATED TO DMF304 ERO47920 KPL 05/23/13		
L	ER 051020 COL 03/07/14		
M	ER 066126 JI 12/19/16		
N	ERO69141 JI 07/24/17		
CUSTOMER SALES DRAWING			
THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.			
SCALE 4:1			
APPROX SURFACE AREA			
WAS: E-19649			
USED ON			
REF:			
PL, 75 BNC			
DRAWN	MRM	DATE	04/15/98
DESIGN	LI	DATE	04/15/98
APPR.		DATE	
		Winchester Electronics Corporation 199 Park Road Ext Suite 104 Middlebury, Connecticut 06762	
2065-10-9			