



MARK: KINGS 126-63-9 (DATE CODE)

NOTES:

- FOR USE WITH RG-142, 223 & 400/U CABLE GROUPS.
- FOR CABLING INSTRUCTIONS SEE CP-5402.
- FOR CABLE TRIMMING USE KTJ-149 & KTD-166.
- FOR CRIMPING USE DIE SIZE KTH-2061.
- INTERFACE PER MIL-STD-348, FIG. 313-1.
- CENTER CONTACT (1-504-31 MA9) SUPPLIED UNASSEMBLED.
- MARK PACKAGE: KINGS 126-63-9
- MATERIALS:
 INSULATORS: TEFLON, ASTM D1710
 GASKET: SILICONE RUBBER, A-A-59588
 C-RING: PHOSPHOR BRONZE, ASTM B103
 K-GRIP SLEEVE: COM. BRONZE ASTM B135
 OUTER CONTACT } BER. COPPER, ASTM B196
 CENTER CONTACT F }
 ALL OTHER METAL PARTS: BRASS, ASTM B16
- FINISHES: CENTER CONTACT: .000050 MIN GOLD PLATE PER ASTM B488 OVER .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
 OUTER CONTACT: .000200 MIN SILVER PLATE PER ASTM B700 OVER .000020 MIN COPPER PER ASTM B734 (RoHS)
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
- ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 WORKING VOLTAGE: 500 VRMS
 FREQUENCY RANGE: DC TO 11 GHZ
- WEIGHT: 36.1 GRAMS

REVISIONS	
ISSUE	CHANGES
3	ER 34606 JCA 04/29/93
4	CN 38026 E TML 07/06/00
5	CN 38250 C BDH 03/14/01
G	REVISED PER DMF304 & ER040887 KPL 03/08/12

126-63-9

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

CAGE CODE: 91836

REF: BOEING

PLUG, ANGLE, TNC, HEX

DRAWN JCA	DATE 10/12/92
DESIGN JT	DATE 10/13/92
APPR.	DATE

KINGS Winchester Electronics Corporation
 62 Barnes Industrial Road North
 Wallingford, Connecticut 06492
 BY WINCHESTER ELECTRONICS

126-63-9