



NOTES:

1. MATERIALS:
 CENTER CONTACT: BERYLLIUM COPPER PER, ASTM B196.
 INSULATOR: TEFLON PER, ASTM D1710.
 CLIP RING & SPRING WASHER: PHOSPHOR BRONZE, PER ASTM B103.
 FERRULE & BODY: BRASS PER, ASTM B16.
2. FINISH:
 CLIP RING: NICKEL PLATE, PER QQ-N-290.
 FERRULE & SPRING WASHER: .000005 GOLD OVER NICKEL.
 BODY & CENTER CONTACT: .000030 MIN. GOLD PER MIL-G-45204
 OVER .000050 MIN. NICKEL PER QQ-N-290
3. ELECTRICAL:
 VSWR: 1.35 MAX. 0 - 1500 MHZ.
 FREQUENCY RANGE: 0 - 1500 MHZ
 DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS
4. FOR USE WITH RG-58 OR EQUIVALENT CABLE.
5. FOR CABLING PROCEDURE USE 5-01.

THIS INFORMATION IS PROPRIETARY AND CONFIDENTIAL. IT IS DISCLOSED TO YOU ON CONDITION NO FURTHER DISCLOSURE IS MADE TO OTHER THAN RETCONN PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM RETCONN INC., TORRINGTON, CT.

SALES DRAWING



RETCONN

A SUBSIDIARY OF SPM
 199 W. PEARL ROAD TORRINGTON, CT. 06790
 TEL. (860) 489-1220 FAX (860) 496-7307

TITLE					
RDM-HF, PLUG, 50 OHM					
DRAWN	CHRIS	DATE	04/22/97	CHECKED	JMC
SCALE	4:1	FSCM	ODWJ4		
APPR.	AT	DWG. NO.	210-510-1160G	REV.	-

UNLESS OTHERWISE SPECIFIED
 TOLERANCES: 3 PLACE DECIMALS ±.005 2 PLACE DECIMALS ±.010
 FRACTIONS ±1/64 ANGLE ±2°
 ALL DIMENSIONS PRIOR TO PLATING
 CHAMFER 1ST THREAD 45° TO ROOT DIAMETER
 REMOVE ALL BURRS AND SHARP EDGES
 ALL DIAMETERS TO BE CONCENTRIC WITHIN .003 TIR
 SURFACE FINISH SHALL BE 63 MICROINCHES MAXIMUM
 DIMENSIONS IN INCHES DO NOT SCALE PRINT

REV.	DESCRIPTION OF CHANGE	DATE	DRN	APPR	MATERIAL
-	RELEASED PER NPR 545	9/16/97	JED	At	
REVISIONS					FINISH